

CS5 (NEW)

Key Features

- ▶ Public address installation speakers
- ▶ Ultra slim and clean design
- ▶ 5" FR transducer
- ▶ Suitable for 70V & 100V high imp. installations
- ▶ Suitable for 8ohm low imp. installations
- ▶ Easy, fast and safe fastening system
- ▶ ABS plastic housing
- ▶ Powder coated iron mesh grille



Tech Specs

TYPE	Public address ceiling speaker
POWER OUTPUT (RMS)	6W (1k6 ohm) / 3W (3k3 ohm) - 100V 3W (1k6 ohm) / 1.5W (3k2 ohm) - 70V 6W - 8ohm
FREQUENCY RANGE	110Hz - 18kHz
NOMINAL IMPEDANCE	HZ 70V/100V LH 8ohm
TRANSDUCER TYPE	5" FR transducer
DISPERSION	150° @ 1kHz, 70° @ 4kHz
MAX. SPL (PEAK)	95dB @ 1m
CONNECTOR	Wiring (power taps)
CONSTRUCTION	ABS plastic
GRILLE	Powder coated iron mesh
INSTALLATION / RIGGING / FLYING	Metal mounting, easy fitting
DIMENSIONS (WDXH)	Ø170x30mm (cut-out) Ø203x80mm
WEIGHT	700g 1.54lb